



## SECTION 08 8300 MIRRORS

### PART 1 GENERAL

#### 1.01 SECTION INCLUDES

- A. Decorative mirrors.

#### 1.02 REFERENCE STANDARDS

- A. ASTM C1036 - Standard Specification for Flat Glass; 2016.
- B. ASTM C1193 - Standard Guide for Use of Joint Sealants; 2016.
- C. ASTM C1503 - Standard Specification for Silvered Flat Glass Mirror, 2008 (Reapproved 2013).
- D. GANA (TIPS) - Mirrors: Handle with Extreme Care (Tips for the Professional on the Care and Handling of Mirrors); 2011.

### PART 2 PRODUCTS

#### 2.01 MANUFACTURERS

- A. Basis of Design Decorative Mirrors:
  - 1. GGI - General Glass International; 101 Venture Way, Secaucus, New Jersey; 800.431.2042, sales@generalglass.com, www.generalglass.com

#### 2.02 MATERIALS

- A. Mirror Design Criteria: Select materials and/or provide supports as required to limit mirror material deflection to 1/200, or to the flexure limit of glass, with full recovery of glazing materials, whichever is less.
- B. Decorative Mirror Glass; Type Satin Mirror: Clear, annealed float glass; ASTM C1036.
  - 1. Thickness: 1/4 inch (6.4 mm).
  - 2. Pattern: Satin Mirror.
  - 3. Edges: Chamfered arris.
  - 4. Size: \_\_\_\_ inch (\_\_\_\_ mm) wide by \_\_\_\_ inch (\_\_\_\_ mm) high nominal.

### PART 3 EXECUTION

#### General Glass International

101 Venture Way | Secaucus, New Jersey | 07094-1808  
800.431.2042 | T: 201.553.1850 | F: 201.553.1851 | generalglass.com

SEE WHAT  
GLASS  
CAN DO



### **3.01 EXAMINATION**

- A. Verify that openings for mirrored glazing are correctly sized and within tolerance.
- B. Verify that surfaces of mirror frames or recesses are clean, free of obstructions, and ready for installation of mirrors.

### **3.02 PREPARATION**

- A. Seal porous mirror frames or recesses with substrate compatible primer or sealer. Prime surfaces scheduled to receive sealant.
- B. Prepare installation in accordance with ASTM C1193 for solvent release sealants, and install sealant in accordance with manufacturer's instructions.

### **3.03 INSTALLATION**

- A. Install mirrors in accordance with GANA (TIPS) and manufacturers recommendations.
- B. Set mirrors plumb and level, and free of optical distortion.
- C. Set mirrors with edge clearance free of surrounding construction including countertops or backsplashes.

### **3.04 CLEANING**

- A. Remove wet glazing materials from finish surfaces.
- B. Remove labels after work is complete. xxx / Satin Mirror 08 8300 - 2 MIRRORS
- C. Clean mirrors and adjacent surfaces.

### **3.05 PROTECTION**

- A. Protect installed mirror from damage during construction
- B. Protect installed mirror from contact with contaminating substances resulting from construction operations.
- C. Remove and replace mirror that is broken, chipped, cracked, abraded, or damaged in other ways during construction period, including natural causes, accidents, and vandalism.

### **END OF SECTION**